

For professionals

For posters, sign boards

For menu cards, price cards

For catalogues, documents

For wider printed materials

# Powerful! Full-scale Output!

Advanced models of LPP1051/6509  
Laminating width widened\* LPP1112  
Always an excellent finish guaranteed  
Easy operation acquired

**The maximum laminating width of 1120mm enables wider lamination. Also good for cold lamination, with the optional Rewinder.**



Rear Cutter

Operation Panel

Hot & Cold LAMINATOR

*Fuji Lamipacker®*

**LPP6512** max.width 650mm

A1 size

Hot & Cold LAMINATOR

*Fuji Lamipacker®*

**LPP1112** max.width 1120mm

Perfect Choice as a Professional Laminator

## Perfect Choice as a Professional Laminator

Hot & Cold LAMINATOR

**LPP6512** max.width **650mm** A1 size

**LPP1112** max.width **1120mm**



### Features

- Max. laminating width is 1120mm for LPP1112 and 650mm for LPP6512.
- Our excellent heating system enables consistently first-class lamination.
- Paper core sizes: 2-1/4 inch, 3 inch for LPP1112  
1 inch, 2-1/4 inch, 3 inch for LPP6512
- Cold lamination is also possible with the optional Rewinder.
- With combination of temperature control and speed control, almost all kinds of lamination is possible.
- Precise setting is possible with Digital Panel.
- Stand-by mode saves power consumption.
- By using thinner film, such as 32 mic, you can save on running costs.



### Specifications

Model	LPP6512	LPP1112
Max. laminating width	650mm(A1)	1120mm
Max. laminating thickness	0.8mm	
Laminating speed	60 - 180cm/min.(adjustable)	
Temperature range	Room temperature, 50 - 130 °C(adjustable)	
Power consumption	2000W	2933W
Power supply	AC 220-240V(50Hz)	
Amperage	8.3A	12.2A
Dimensions	1004(W)x615(D)x412(H)mm	1480(W)x615(D)x412(H)mm
Weight	76.8kg	88.7kg
JAN(EAN)Code	4514015200370	4514015200387
Attachment	Film Setting Board / Stand / Manual / Attachment for 3 inch paper core	
Option	Rewinder	

\*Specifications may be modified without prior notice.

**Advanced models of LPP6509/1051**  
**Laminating width widened**  
**Easy operation acquired**  
**Always an excellent finish guaranteed**

### Laminating Film

- It is recommended to use our original roll film. Mismatching of film characteristics may lead to problems such as jamming or imperfect lamination.
- By choosing our lamination film, it is possible to obtain not only waterproof effect but also UV cut or anti-static effect.

### Safety Precautions

- Please read instruction manual thoroughly before operation to avoid danger to yourself and failure in the lamination process.
- Should any of the following symptoms occur, unplug the Lamipacker and contact your Fujipla dealer.
  - The power cord or plug gets unusually hot.
  - A strange smell or smoke comes out of the machine.
  - Water or a foreign substance gets inside the machine.
- Warning and caution labels are omitted on the photos in this catalogue.
- Specifications or appearance of the product may change for improvement reasons without notice.
- Parts for maintenance service are available for a minimum of 5 years after cessation of the manufacture of product.

### Contact:

ID Card System, Laminating Machine & Film

**FUJIPLA Inc.**  
TOKYO, JAPAN



<http://www.fujipla-japan.com>

The description in the catalogue is the one as of November 2006.